

TABLE II
REQUIRED MOTOR VEHICLE LIGHTING EQUIPMENT
(as adopted in Chapter 153)

ITEM	Multi-Purpose Passenger Vehicles, Trucks and Buses-80" or More Overall Width
Headlamps.....	2 white 7" Type 2 headlamp units or 2 white, 5 3/4" Type 1 headlamp units and 2 white 5 3/4" Type 2A headlamp units and 2 white Type 1A headlamp units. 2 white headlamps, Type 2B1 or Type 2D1; or 4 white headlamps; 2 each Type 1C1 and Type 2C1, or Type 2A1.
Tail Lamps.....	2 red
Stoplamps	2 red
License Plate Lamp	1 white
Reflex Reflectors.....	4 red; 2 amber
Side Marker Lamps	2 red; 2 amber
Backup Lamp.....	1 white
Turn Signal Lamps	2 red or amber; 2 amber
Turn Signal Operating Unit.....	1
Turn Signal Flasher.....	1
Vehicular Hazard Warning Signal Operating Unit.....	1
Vehicular Hazard Warning Signal Flasher.....	1
Identification Lamps.....	3 amber; 3 red
Clearance Lamps	2 amber; 2 red
Intermediate Side Marker Lamp	2 amber
Intermediate Reflex Reflectors	2 amber

TABLE III LOCATION OF REQUIRED EQUIPMENT

Multi-purpose Passenger Vehicles, Trucks, Trailers and Buses-80" or More Overall Width

ITEM	LOCATION ON	Height above road surface measured from center of item on vehicle
	Multi-purpose passenger vehicles, trucks and buses	
Headlamps	Type 1 headlamps at the same height. 1 on each side of the vertical centerline. Type 2 headlamps at the same height. 1 on each side of the vertical centerline, as far apart as practicable.	Not less than 24" nor more than 54"
Taillamps	On the rear, 1 on each side of the vertical centerline, at the same height, and as far apart as practicable.	Not less than 15" nor more than 72"
Stop Lamps	On the rear, 1 on each side of the vertical centerline, at the same height, and as far apart as practicable.	Not less than 15" nor more than 72"
License Plate Light	At rear license plate, to illuminate the plate from the top or sides.	No Requirement
Backup Lamp	On the rear	No Requirement
Turn Signal Lamps	At or near the front 1 amber on each side of the vertical centerline, at the same height and as far apart as practicable. On the rear 1 red or amber on each side of the vertical centerline, at the same height, and as far apart as practicable.	Not less than 15" nor more than 83"
Identification Lamps	On the front and rear 3 lamps, amber in front, red in rear, as close as practicable to the top of the vehicle, at the same height as close as practicable to the vertical centerline, with lamp centers spaced not less than 6" or more than 12" apart.	No Requirements
Clearance Lamps	On the front and rear 2 amber lamps on front, red in rear, as close as practicable to the top of the vehicle, 1 on each side of the vertical center- line, at the same height, and as near the top as practicable.	No Requirements
Intermediate Side Marker Lamps	On each side 1 amber located at or near the midpoint..... between the front and rear side marker lamps.	Not less than 15"
Intermediate Side Reflex Reflectors	On each side 1 amber located at or near the midpoint..... between the front and rear side reflex reflector.	Not less than 15" nor more than 60"
Reflex Reflectors	On the rear 1 red on each side of the vertical center- line, as far apart as practicable, and at the same height.	Not less than 15" nor more than 60"
Side Marker Lamps	On each side 1 red as far to the rear as practicable, and 1 amber as far to the front as practicable.	Not less than 15" and on the rear of trailers not more than 60"