

TABLE IV
REQUIRED MOTOR VEHICLE LIGHTING EQUIPMENT

(as adopted in Chapter 153)

ITEM	Passenger cars, motorcycles and multi-purpose vehicles, trucks, trailers, and buses of less than 80" overall width
Headlamps	2 white, 7", Type 2 headlamp units or 2 white 5 3/4", Type 1 headlamp units or 2 white 5 3/4" Type 2A headlamp units and 2 white Type 1A headlamp units. 2 white headlamps, Type 2B1 or Type 2D1; 4 white headlamps, 2 each Type 1C1 and Type 2C1, or Type 1A1 and Type 2A1.
Taillamps	2 red
Stop Lamps	2 red
License Plate Light	1 white
Parking Lamps	2 amber or white
Reflex Reflectors	4 red; 2 amber
Intermediate Side Reflex Reflectors	2 amber
Intermediate Side Marker Lamps	2 amber
Side Marker Lamps	2 red; 2 amber
Backup Lamp	1 white
Turn Signal Lamps	2 red or amber
Turn Signal Operating Unit	1
Turn Signal Flasher	1
Vehicular Hazard Warning Signal Operating Unit	1
Vehicular Hazard Warning Signal Flasher	1

TABLE V - LOCATION OF REQUIRED EQUIPMENT (continued)

Passenger Cars, Multi-Purpose Passenger Cars, Trucks, Trailers, and Buses of less than 80" overall Width

ITEM	LOCATION ON	Height above road surface measured from center of item on vehicle
	Passenger cars, multi-purpose passenger vehicles, trucks, trailers and buses	
* Turn Signal Lamps	At or near the front, 1 amber on each side of the vertical centerline, at the same height, and as far apart as practicable.	Not less than 15" nor more than 83"
	On the rear, 1 red or amber on each side of the vertical centerline, at the same height, and as far apart as practicable.	Not less than 15" nor more than 83"
Headlamps	Type 1 headlamp at the same height, 1 each side of the vertical centerline, at the same height, and as far apart as practicable.	Not less than 24" nor more than 54"
Tail Lamps	On the rear, 1 on each side of the vertical center- line, at the same height, and as far apart as practicable.	Not less than 15" nor more than 72"
Stop Lamps	On the rear, 1 on each side of the vertical center- line, at the same height, and as far apart as practicable.	Not less than 15" nor more than 72"
License Plate Light	At rear license plate, to illuminate the plate from the top or sides.	No Requirement
Reflex Reflectors	On the rear, 1 red on each side of the vertical center- line, at the same height, and as far apart as practicable. On each side, 1 red as far to the rear as practicable, and 1 amber as far to the front as practicable.	Not less than 15" nor more than 60"
Parking Lamps	On the front, 1 on each side of the vertical center- line, at the same height, and as far apart as practicable.	Not less than 15"
Backup Lamps	On the rear	No Requirement
Side Marker Lamps	On each side, 1 red as far to the rear as practicable, and 1 amber as far to the front as practicable.	Not less than 15"
Intermediate Side Marker Lamps	On each side, 1 amber located at or near the midpoint between the front and rear side marker lamps.	Not less than 15"
Intermediate Side	On each side, 1 amber located at or near the midpoint between the front and rear side marker reflector.	Not less than 15"

* Front Turn Signal Lamps Not Required for Trailers.