

Required items for a PA Street Rod Title

To qualify for a street rod title, the street rod must be made from a 1948 or older model year body or be a reproduction of a 1948 or older model year body. It must also have a gross weight rating of less than 9,001 lbs.

<u>Street Rods must meet all regulations listed in Subchapters E & K of vehicle code EXCEPT for the following items</u>

***Link to code book is on enhanced inspection page

- 1. No bumpers are necessary
- 2. No fenders are necessary
- 3. No engine cover is necessary (if hood is missing an adequate fan shroud must be present)
- Certificate of Title or Certificate of Origin

(This documentation is not required, but without it you will receive a "Specially Constructed/Street Rod" branded title. You must have some source of documentation on where all the parts used, came from)

- **Bill of sale** (if purchasing, already built, etc.)
- **Copy of all receipts** (from building it or for any modifications made since it was purchased)
- **Explanation Build Sheet** on 8-1/2"x11" sheet of paper (*Explaining in easy terms, body type, frame type, engine type, suspension type, etc. and how/who assembled*)
- **Optional Explanation Sheet** Used to explain if you do not have documentation or receipts for all parts. If you do not have receipts for some parts, you need to explain why. You will need to pay sales tax on an estimated value of those parts. The state has the right to deny accepting this but they are normally fairly reasonable if explanation is reasonable.
- Commonly Missed Items are below
 - Windshield height (not less than 7" in vertical height)
 - Must have a windshield wiper
 - o Must have a defrost system (may be clip on unit, JC Whitney sells one)

- Fuel tank must be an approved tank (see section 175.80 of Vehicle code, cannot be a self-fabricated tank)
- Fuel tank and lines cannot be in or pass through passenger area or cargo area (see section 175.80 of Vehicle code, cargo area includes trunk or bed of truck)
- o Fuel filter must be externally mounted
- Glass needs to be of approved type for area (Safety Glass must be used everywhere, laminated safety glass for windshield etc.)
- Window tint must meet same criteria as standard regulation (**See link on enhanced page for window screening regulations)
- Fan shroud must be covering fan so hands cannot get in fan if engine is not totally covered
- Mufflers (see section 175.75 of Vehicle code)
- Scrub line (see section 175.209 of vehicle code)
- Obstructions forward of the windshield (e.g. hood scoops, etc. cannot project upward more than 2" from the bottom of the drivers line of sight)
- o Minimum of 1 mirror is required
- Tire width (the front tires have a minimum width of 5". The rear tires cannot be wider than 9" unless a dual cylinder master cylinder brake system is used)